

DOMINIQUE **D**

Sneaker with optimal cushioning and comfort

Dominique is a trendy sneaker, adapted to the needs of many professionals. This closed shoe provides maximum protection and fits perfectly. The air unit and the removable foam footbed provides optimal cushioning and gives great comfort. The slip-resistant outsole with an antistatic plug can easily be cleaned with a damp cloth. The breathable lining completes this ultimate professional sneaker to serve any in need of comfort during and beside their working day.

Upper	Printed Action Leather
Outsole	PU/Rubber
Тоесар	
Midsole	
Lining	3D-Mesh, Mesh
Footbed	SJ foam footbed
Standards	O1 / ESD, SRC
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0





ELECTROSTATIC DISCHARGE (ESD)

Static discharges can ignite flammable mixtures and damage electronic components. ESD footwear prevents a build-up of static electrical charges in the human body by sending them to the ground in a very safe and controlled manner.



OXYGRIP SOLE

The rubber outsole with oxytraction® technology provides excellent traction on both dry and wet floors and meets SRC (SRA+ SRB) standards.



SJ FOAM

Z

The SJ Foam footbed combines extra comfortable heel and arch support with air breathability. They are designed to give minimal impact with the ground while offering maximum comfort.

BLK



SRC

Slip resistant soles are one of the most vital elements in safety footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



BREATHABLE UPPER

It's important to keep your feet as cool as possible when you work up a sweat. A breathable upper keeps your feet cool and fresh so the chance of smelly feet, foot odor, or fungal infection won't ruin your daily after-work life.





WWW.SAFETYJOGGER.COM





DOMINIQUE 🚺

Industries:

Catering, Cleaning, Food & beverages, Healthcare, Medical



Indoor, Outdoor

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Jpper	Printed Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	1.1	>= 0.80
	Upper: water vapor coefficient	mg/cm ²	16.8	>= 15.00
Lining	3D-Mesh, Mesh			
	Lining: permeability to water vapor	mg/cm²/h	67.9	>= 2.00
	Lining: water vapor coefficient	mg/cm ²	543	>= 20.00
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	>= 400.00
Outsole	PU/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	120	<= 150.00
	Outsole slip resistance SRA: heel	friction	0.29	>= 0.28
	Outsole slip resistance SRA: flat	friction	0.33	>= 0.32
	Outsole slip resistance SRB: heel	friction	0.21	>= 0.13
	Outsole slip resistance SRB: flat	friction	0.23	>= 0.18
	Antistatic value	MegaOhm	NA	1000.00 >< 0.10
	ESD value	MegaOhm	73.6	< 100.00
	Heel energy absorption	J	36	>= 0.20
Гоесар				
	Impact resistance toecap (clearance after impact 100J)	mm	NA	>= 14.00
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	>= 14.00
	Impact resistance toecap (clearance after impact 200J)	mm	NA	>= 14.00
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	>= 14.00

Sample size: 41

ENGINEERED IN EUROPE

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM